

# All-in-One

## Water based

Sparcolux All-In-One can be applied directly to a range of cementitious substrates, woods, and previously painted substrates (including enamels). This product can also be used with a waterproofing membrane as a waterproofer for exterior wall cappings and parapets.



### FEATURES & BENEFITS

- Easy-to-use one coat system from primer to top coat
- Excellent adhesion, even on difficult substrates
- Tough, flexible and durable
- High hiding for obliterating surface imperfections
- High fill system for excellent hiding power/ obliteration
- Good waterproofing properties
- Excellent weatherability - UV, mould & fungus resistance



### PRODUCT USES

<b>Sealer &amp; Primer</b>	Suitable on cured plaster, suitably prepared gypsum, fibre cement boards, bagged finishes, precast concrete, brick, etc.
<b>Undercoat</b>	Previously painted water-based surfaces and enamel-based surfaces.
<b>Waterproofing</b>	For wall cappings and parapets made from cured plaster, concrete, brick or fibre cement.
<b>Topcoat</b>	High filling and high hiding smooth matt finish in a range of attractive colours.



### PHYSICAL PROPERTIES

<b>Colour</b>	10 standard colours, including White
<b>Appearance</b>	Matt
<b>Viscosity</b>	95 -105 KUs at 25°C
<b>SG</b>	1.40 - 1.45
<b>Mass Solids</b>	50-60%
<b>Volume Solids</b>	50-60 %
<b>Shelf Life</b>	1 year
<b>Storage Conditions</b>	Normal
<b>Pack Size</b>	5 Litre, 20 Litre



### SURFACE PREPARATION

Ensure all substrates are thoroughly clean, sound and free of any contaminants such as dirt, grease, salts, and algae. Repair any cracks on the surface and clean using Sparcolux Sugar Soap.

#### NEW CEMENT

- New plaster or concrete surfaces must cure for a minimum of 21 days or once moisture content is less than 10% prior to applying **Sparcolux All-In-One**.

#### NEW PLASTER, GYPSUM PLASTER, FIBRE CEMENT BRICK WORK

- Ensure gypsum is suitably prepared (using prescribed slurry ratio and ensure the end product is not too DRY). Ensure all substrates are adequately cured, clean and free of contaminants.
- If not, clean the substrate well and allow to dry. Prime the substrate with **Sparcolux All-In-One**.

#### PREVIOUSLY PAINTED

- Remove algae, lichen, loose materials and flaking paint with a scrubbing brush or high pressure hose. Wash area with Sparcolux Sugar Soap. If required, apply an anti-fungal wash, then rinse with water.
- Seal powdery surfaces with Sparcolux Keybond or Sparcolux Undercoat.
- Glossy surfaces should be gently sanded, cleaned and dried.



031 943 4449



enquiries@sparcolux-paints.co.za

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.

# DATASHEET WALL & CEILING PAINT

08/07/2025



## APPLICATION PROPERTIES

<b>Method</b>	Brush, Roller, Spay
<b>Spreading Rate</b>	Primer Coat: 4-6m <sup>2</sup> per litre. Top Coat: 8-12m <sup>2</sup> per litre. Depending on surface porosity.
<b>Number of coats</b>	1 Primer coat, 1-2 topcoats, unless specified otherwise
<b>Drying time</b>	Touch dry 1 -2 hours at 25°C Allow to cure for 7 days before washing.
<b>Overcoating</b>	3-4 hours at 25°C
<b>Thinning</b>	Brush, Roller - not recommended Spraying - 10% by volume.
<b>Cleaning</b>	Water



## APPLICATION INSTRUCTIONS

- Stir very well before use!!!
- Do not dilute - this product is ready to use.
- Apply product with a brush, roller or spray system
- For topcoat application: Apply 2 coats for complete obliteration, unless over coating a dark colour with a pastel shade, in which case apply 3 coats.
- Allow 3 - 4 hours drying time between coats.
- Clean brushes with water. Product thinning is not recommended



## SAFETY

### Read all instructions before use.

- Replace lid when not in use.
- Use product in well ventilated areas.
- If medical advice is needed, have product packaging at hand.
- Do not eat or drink when using product.
- Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.
- IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms persist.
- IF ON SKIN Take off immediately all contaminated clothing and wash before reuse. Wash skin with soapy water. Seek medical attention if symptoms persist.
- IF SWALLOWED Do not induce vomiting and seek immediate medical attention.
- Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre 0861 555 777.



## STORAGE INSTRUCTIONS

Ensure the lid is tightly sealed and the product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty containers and do not use them for any other purpose. Do not dispose into common waste system, contact 031 943 4449 for disposal information.



The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.



031 943 4449



enquiries@sparcolux-paints.co.za

**SPARCOLUX**  
EST 1980  
DECORATIVE & INDUSTRIAL PAINTS