

Smart Koat

Quality PVA for walls and ceilings

Smart Koat is a general purpose hi-cover contractor filler coat. This functional high-solids wall and ceiling coating obliterates, levels and hides surface imperfections, giving a smooth matt finish.

Smart Koat is ideal for newly primed or previously painted interior and exterior walls requiring a quick-drying matt finish. This product is also an ideal top coat for interior ceiling boards. This product is water-based, low splatter and low-odour making it easy to apply and clean.



FEATURES & BENEFITS

- Low cost PVA, specifically formulated for contractor requirements.
- Quick drying time.
- Good obliteration and over-coating properties.



PHYSICAL PROPERTIES

| | |
|---------------------------|---------------------|
| Colour | White |
| Appearance | Matt |
| Viscosity | 90 -105 KUs at 25°C |
| SG | 1.40 - 1.45 |
| Mass Solids | 45 - 50% |
| Volume Solids | 30- 35 % |
| Shelf Life | 1 year |
| Storage Conditions | Normal |
| Pack Size | 5 Litre, 20 Litre |



APPLICATION PROPERTIES

| | |
|------------------------|--|
| Method | Brush, Roller, Spay |
| Spreading Rate | 8-10 m2 per litre |
| Number of coats | 2, unless specified otherwise |
| Drying time | Touch dry: 30-60 minutes |
| Overcoating | 3-4 hours at 25°C |
| Thinning | Brush, Roller - not recommended Spraying: - 10% Water by volume |
| Cleaning | Water |



APPLICATION INSTRUCTIONS

- Stir very well before use!!
- Do not dilute - this product is ready to use.
- Apply product with a brush, roller or spray system
- Apply 2 coats for complete obliteration, unless over coating a dark colour with a pastel shade, in which case apply 3 coats
- Allow 3 - 4 hours drying time between coats.
- Clean brushes with water. Product thinning is not recommended.



STORAGE INSTRUCTIONS

Ensure the lid is tightly sealed and the product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place out of reach of children. Dispose of empty containers and do not use them for any other purpose. Do not dispose into common waste system contact 031 701 2046 for disposal information.



031 701 2046



enquiries@sparcolux-paints.co.za

DATASHEET WALLS AND CEILINGS

05/11/2024



SURFACE PREPARATION

Read all instructions before use.

- Ensure all substrates are thoroughly clean, sound and free of any contaminants such as dirt, grease, salts, and algae. Repair any cracks on the surface and clean using Sparcolux Sugar Soap.

| | |
|---|---|
| New Cement | New cements must be allowed to cure for a minimum 21 days. Once sufficiently clean and dry, prime substrate with Sparcolux WB Plaster Primer or Sparcolux SB Plaster Primer. Refer and follow the directions per the primer used. |
| New plaster, gypsum plaster, fibre cement brick work | Clean the substrate well and allow to dry. Once sufficiently clean and dry, prime substrate with Sparcolux WB Plaster Primer or Sparcolux SB Plaster Primer. Refer and follow the directions per the primer used. |
| Previously painted surfaces | Remove algae, lichen, loose materials and flaking paint with a scrubbing brush or high pressure hose. Wash area with Sparcolux Sugar Soap. If required, apply an anti-fungal wash, then rinse with water. Seal powdery surfaces with Sparcolux Keybond or with Sparcolux SB Plaster Primer. Glossy surfaces should be gently sanded, cleaned and dried. |



SAFETY

Read all instructions before use.

- Replace lid when not in use.
- Use product in well ventilated areas.
- If medical advice is needed, have product packaging at hand.
- Do not eat or drink when using product.
- Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.
- IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms persist.
- IF ON SKIN Take off immediately all contaminated clothing and wash before reuse. Wash skin with soapy water. Seek medical attention if symptoms persist.
- IF SWALLOWED Do not induce vomiting and seek immediate medical attention.
- Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre 0861 555 777.



The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.



031 701 2046



enquiries@sparcolux-paints.co.za

EST 1980
SPARCOLUX[®]
DECORATIVE & INDUSTRIAL PAINTS